



### Rubber Lined Double Flange Butterfly Valve with Electric Actuator

Size	3" to 72"
MOC	CI / DI / WCB / CF8M
Seals	Nitrile / NBR / EPDM / Viton
Pressure	PN 6 / 10 / 16 / 20 & 25
Temperature	-20°C to 80°C (Depending on MOC)
Ends	Wafer Type Double Flange



### PTFE (FEP - PFA) Lined Butterfly Valve with Electric Actuator

Size	2" to 20"
MOC	WCB / CF8 / CF8M / CF3M
Seals	FEP / PFA
Pressure	10 Kg/cm <sup>2</sup>
Temperature	FEP 180°C / PFA 230°C
Ends	Wafer Type



### UPVC Body Butterfly Valve with Electrical Actuator

Size	1 ½" to 12"
MOC	UPVC / PP
Seals	NBR / EPDM
Pressure	Upto 10Kg/cm <sup>2</sup>
Temperature	Upto 180°C
Ends	Wafer Type



### Rubber Lined Wafer Type Butterfly Valve with Electric Actuator

Size	1 ½" to 72"
MOC	CI / DI / WCB / CF8M
Seals	Nitrile / NBR / EPDM / Viton
Pressure	PN 6 / 10 / 16 / 20 & 25
Temperature	-20°C to 80°C (Depending on MOC)
Ends	Wafer Type



### Double Offset Disc Butterfly Valve with Electrical Actuator

Size	2½" to 88"
MOC	WCB / CF8 / CF8M / CF3M
Seals	NBR / PTFE / RPTFE
Pressure	PN 10 / 16 / 20 & 25
Temperature	Upto 180°C / 250°C
Ends	Wafer Type / Double Flange



### High Performance Butterfly Valve with Electrical Actuator

Size	1½" to 24"
MOC	WCB / CF8 / CF8M / CF3M
Seals	NBR / PTFE / RPTFE / EPDM / VITON
Pressure	PN 6 / 10 / 16 / 20 & 25
Temperature	Upto 180°C / 250°C
Ends	Wafer Type / Double Flange lug type



### AWWA C504 Standard Larger Dia Butterfly Valve with Electrical Actuator

Size	1½" to 88"
MOC	IS Grade MS / WCB / CF8
Seals	NBR / EPDM / Nitrile Viton
Pressure	PN 6 / 10 / 16 / 20 & 25
Temperature	-20°C to 80°C (Depending on MOC)
Ends	Double Flange AWWA C207



### Triple Offset Butterfly Valve with Electrical Actuator

Size	1½" to 12"
MOC	Aluminium Alloy
Seals	Nitrile / NBR / EPDM / Viton
Pressure	PN 10 / 16
Temperature	Upto 180°C
Ends	Wafer Type